

BIC - 2109-N NVR



Key Features

Original

- SDA+ over LAN technology inside, One-click Access third-party ONVIF camera
- All channel real-time synchronous playback
- Support IE, Chrome, Firefox, Safari, and browser plug-in free
- All channel synchronous live view and playback by smart phone

HD Input & Output

- H.265 / H.264 video formats
- Up to 9 8MP IP camera can be accessed
- HDMI at up to 4K, VGA at up to 1080P

HD Storage & Communication

- 1 HDD supported, Up to 8TB for each
- 1 self-adaptive 10/100M RJ45 interface

Special

- Instant playback for assigned channel during multi-channel live view mode
- Smart search for selected area in the video, and smart playback to improve the efficiency

Specifications

Model		BIC-2109-N	
Video / Audio input	IP video input	9 Ch. Up to 8 MP	
	IP audio input	9 Ch.	
	Two-way audio	1x RCA (2.0 Vp-p, 1 kΩ)	
Network	Incoming	Standard	ONVIF, RTSP, HB-protocol
		Bandwidth	80Mbps
	Outgoing	Standard	CGI, RTSP, RTMP(Only for H.264), HB-SDK
		Bandwidth	80Mbps
Video / Audio output	Recording resolution	Up to 8 MP	
	HDMI output	4K (3840 x 2160)/60Hz, 1080p (1920 x 1080)/60Hz, 720p (1280 x 720)/60Hz, UXGA (1600 x 1200)/60Hz, 1280 x 1024/60Hz	
	VGA output	1080p (1920 x 1080)/60Hz, 720p (1280 x 720)/60Hz, UXGA (1600 x 1200)/60Hz, 1280 x 1024/60Hz	
	Audio output	1x RCA (Linear, 1 kΩ)	
Decoding	Decoding standard	H.265 / H.264	
	Live view / playback resolution	Up to 8 MP	
	Synchronous playback	All Ch. Synchronous playback	
HDD	SATA	1 SATA interface for 1 HDD	
	Capacity	Up to 8TB capacity for each HDD	
External interface	Network	1 10/100Mbps self-adaptive RJ45 interface	
	USB	Rear panel: 1x USB3.0 / 1x USB2.0	
	Alarm	2 in / 1 out	
	RS-485	N/A	
General	Power supply	12V 24W	
	Operating condition	-Temperature: -10°C – 55°C (-14°F – 131°F) Humidity: 10 - 90%	
	Dimensions (WxDxH)	254 x 180 x 49.5mm (10" x 7" x 1.9")	